





SPECIFICATION	VALUE
AMPS/PHASE	0.67
RESISTANCE/PHASE(Ohms)@25°C	5.60±10%
INDUCTANCE/PHASE(mH)@1KHz	4.20±20%
HOLDING TORQUE w/o GEARBOX(Nm)[lb-in]	0.07[0.62]
GEAR RATIO	26 ¹⁰³ / ₁₂₁
EFFICIENCY	80.00%
STEP ANGLE w/o GEARBOX(°)	1.80
BACKLASH@NO-LOAD	<=3°
MAX.PERMISSIBLE TORQUE(Nm)	3.00
MOMENT PERMISSIBLE TORQUE(Nm)	5.00
SHAFT MAXIMUM AXIAL LOAD(N)	5.00
SHAFT MAXIMUM RADIAL LOAD(N)	25.00
AMBIENT TEMPERATURE	-10°C~50°C[14°F~122°F]
INSULATION CLASS	B 130°C[266°F]
TEMPERATURE RISE	MAX.80°C

FULL STEP 2 PHASE-Ex.,WHEN FACING MOUNTING END (X)						MOTOR CONNECTION			
STEP	A+	B+	A-	B-		PIN NO	BIPOLAR	LEADS	
1	+	+	-	-	↓ ↑ CW CCW	1	A+	BLK	
2	-	+	+	-		2	A-	GRN	
3	-	-	+	+		3	B+	RED	
4	+	-	-	+		4	B-	BLU	

UNIT mm
GB/T 1804-M
EQV.ISO 2768-1
CLASS M:
<=6 ±0.1
>6~30 ±0.2
>30~120 ±0.3
>120~400 ±0.5

OSMTEC®
Stepper Motor Specialists



mm			
UNITS	DRN	YSX	1.12.2026
3:2	APVD	LJ	1.12.2026
SCALE	SIGNATURE		DATE

GEARBOX MOTOR
11HS12-0674D1-PG27