


FULL STEP 2 PHASE-Ex., WHEN FACING MOUNTING END (X)

STEP	A+	B+	A-	B-		CCW
1	+	+	-	-		
2	-	+	+	-		
3	-	-	+	+		
4	+	-	-	+		

UNIT mm  
 GB/T 1804-M EQV.ISO  
 2768-1 CLASS M:  
 <=6 ±0.1  
 >6~30 ±0.2  
 >30~120 ±0.3  
 >120~400 ±0.5

WINDING			CONNECTION	
			SPECIFICATION	BIPOLAR
			AMPS/PHASE	1.50
			RESISTANCE/PHASE(Ohms)@25°C	1.60±10%
			INDUCTANCE/PHASE(mH)@1KHz	2.30±20%
			HOLDING TORQUE(Nm)[lb-in]	0.20[1.77]
			STEP ANGLE(°)	1.8
			STEP ACCURACY(NON-ACCUM)	±5.00%
PIN NO	BIPOLAR	LEADS	LEAD(mm)	
1	A+	RED	LINEAR TRAVEL/STEP(mm)	0.01
2	A-	RED/WHT	AMBIENT TEMPERATURE	-10°C~50°C[14°F~122°F]
3	B+	GRN	INSULATION CLASS	B 130°C[266°F]
4	B-	GRN/WHT	TEMPERATURE RISE	MAX.80°C

**OSMTEC**®  
 Stepper Motor Specialists



mm			
UNITS	DRN	LJ	1.14.2026
1:1	APVD	MYX	1.14.2026
SCALE	SIGNATURE	DATE	

**LINEAR STEPPER MOTOR**

**14E19S1504BAM5-150RS**