



DWG NO. -




FULL STEP 2 PHASE-Ex., WHEN FACING MOUNTING END (X)

STEP	A+	B+	A-	B-		CCW
1	+	+	-	-	 CW	↑
2	-	+	+	-		
3	-	-	+	+		
4	+	-	-	+		

UNIT mm
 GB/T 1804-M EQV.ISO
 2768-1 CLASS M:
 <=6 ±0.1
 >6~30 ±0.2
 >30~120 ±0.3
 >120~400 ±0.5

WINDING			CONNECTION	BIPOLAR
			SPECIFICATION	
			AMPS/PHASE	1.20
			RESISTANCE/PHASE(Ohms)@25°C	3.00±10%
			INDUCTANCE/PHASE(mH)@1KHz	3.00±20%
			HOLDING TORQUE(Nm)[lb-in]	0.11[0.95]
			STEP ANGLE(°)	0.90
PIN NO	BIPOLAR	LEADS	ROTOR INERTIA(g-cm ²)	14.00
1	A+	BLK	WEIGHT(Kg)[lb]	—
2	B+	GRN	AMBIENT TEMPERATURE	-10°C~50°C[14°F~122°F]
3	A-	BLU	INSULATION CLASS	B 130°C[266°F]
4	B-	RED	TEMPERATURE RISE	MAX.80°C

OSMTEC®
 Stepper Motor Specialists



mm

UNITS	DRN	YSX	1.13.2026
1:1	APVD	LJ	1.13.2026
SCALE	SIGNATURE		DATE

STEPPER MOTOR

17HM08-1204S