

SPECIFICATION	VALUE
AMPS/PHASE	4.20
RESISTANCE/PHASE(Ohms)@25°C	0.88±10%
INDUCTANCE/PHASE(mH)@1KHz	3.40±20%
HOLDING TORQUE w/o GEARBOX(Nm)[lb-in]	3.00[26.55]
GEAR RATIO	15
EFFICIENCY	76%
STEP ANGLE w/o GEARBOX(°)	1.80
BACKLASH@NO-LOAD	1°
MAX.PERMISSIBLE TORQUE(Nm)[lb-in]	18.00[159.31]
SHAFT MAXIMUM RADIAL LOAD(kN)	0.86
AMBIENT TEMPERATURE	-10°C~50°C[14°F~122°F]
INSULATION CLASS	B 130°C[266°F]
TEMPERATURE RISE	MAX.80°C


FULL STEP 2 PHASE-Ex.,WHEN FACING MOUNTING END (X)

STEP	A+	B+	A-	B-	CW	CCW
1	+	+	-	-	↓ ↑	↑ ↓
2	-	+	+	-		
3	-	-	+	+		
4	+	-	-	+		

UNIT mm
GB/T 1804-M EQV.ISO
2768-1 CLASS M:
<=6 ±0.1
>6~30 ±0.2
>30~120 ±0.3
>120~400 ±0.5

MOTOR CONNECTION

PIN NO	BIPOLAR	LEADS
1	A+	BLK
2	A-	GRN
3	B+	RED
4	B-	BLU



OSMTEC[®]
Stepper Motor Specialists

mm			
UNITS	DRN	ZPJ	1.12.2026
2:3	APVD	YSX	1.12.2026
SCALE	SIGNATURE	DATE	

GEARBOX MOTOR
23HS45-4204S-RVS30-G15