


FULL STEP 2 PHASE-Ex., WHEN FACING MOUNTING END (X)

STEP	A+	B+	A-	B-		CCW
1	+	+	-	-	 	↑
2	-	+	+	-		↓
3	-	-	+	+		
4	+	-	-	+		

UNIT mm
 GB/T 1804-M EQV.ISO
 2768-1 CLASS M:
 ≤6 ±0.1
 >6~30 ±0.2
 >30~120 ±0.3
 >120~400 ±0.5

WINDING			CONNECTION	BIPOLAR
			SPECIFICATION	
			AMPS/PHASE	2.00
			RESISTANCE/PHASE(Ohms)@25°C	3.60±10%
			INDUCTANCE/PHASE(mH)@1KHz	12.00±20%
			HOLDING TORQUE(Nm)[lb-in]	1.20[10.62]
			STEP ANGLE(°)	1.80
			STEP ACCURACY(NON-ACCUM)	±5.00%
PIN NO	BIPOLAR	LEADS	LEAD(mm)	2
1	A+	BLK	LINEAR TRAVEL/STEP(mm)	0.01
2	A-	GRN	AMBIENT TEMPERATURE	-10°C~50°C[14°F~122°F]
3	B+	RED	INSULATION CLASS	B 130°C[266°F]
4	B-	BLU	TEMPERATURE RISE	MAX.80°C

OSMTEC®
 Stepper Motor Specialists



mm

UNITS	DRN	MYX	1.9.2026
2:3	APVD	LDJ	1.9.2026
SCALE	SIGNATURE		DATE

LINEAR STEPPER MOTOR

23N22S2004AJ4-355RS