





DWG NO. -



ENCODER RESOLUTION:1000PPR (4000CPR)

15-PIN DB MALE PLUG	1	2	3	11	12	13
DESCRIPTION	EA+	VCC	GND	EB+	EB-	EA-


FULL STEP 2 PHASE-Ex., WHEN FACING MOUNTING END (X)

STEP	A+	B+	A-	B-		CCW
1	+	+	-	-		
2	-	+	+	-		
3	-	-	+	+		
4	+	-	-	+		

UNIT mm
GB/T 1804-M EQV.ISO
2768-1 CLASS M:
≤6 ±0.1
>6~30 ±0.2
>30~120 ±0.3
>120~400 ±0.5

WINDING			CONNECTION		BIPOLAR
			SPECIFICATION		
			AMPS/PHASE		5.00
			RESISTANCE/PHASE(Ohms)@25°C		0.52±10%
			INDUCTANCE/PHASE(mH)@1KHz		2.10±20%
			HOLDING TORQUE(Nm)[lb-in]		3.00 [26.57]
			STEP ANGLE(°)		1.80
STEP ACCURACY(NON-ACCUM)		±5.00%			
PIN NO	BIPOLAR	LEADS	ROTOR INERTIA(g·cm²)		—
1	A+	--	WEIGHT(Kg)[lb]		—
2	A-	--	AMBIENT TEMPERATURE		-10°C~50°C[14°F~122°F]
3	B+	--	INSULATION CLASS		B 130°C[266°F]
4	B-	--	TEMPERATURE RISE		MAX.80°C

OSMTEC®
Stepper Motor Specialists



mm			
UNITS	DRN	ZPJ	1.15.2026
2:3	APVD	YSX	1.15.2026
SCALE	SIGNATURE	DATE	

STEPPER MOTOR

24HS34-5004D-E1000