


BRAKE CONNECTIONS


24V 7.0N.m



FULL STEP 2 PHASE-EX. WHEN FACING MOUNTING END (X)

STEP	A+	B+	A-	B-	CCW	CW
1	+	+	-	-	 	UNIT mm GB/T 1804-M EQV. ISO 2768-1 CLASS M: ≤6 >6~30 >30~120 >120~400
2	-	+	+	-		±0.1 ±0.2 ±0.3 ±0.5
3	-	-	+	+		
4	+	-	-	+		

WINDING



PIN NO	BIPOLAR	LEADS	AMBIENT TEMPERATURE
1	A+	BLK	-10°C~50°C [14°F~122°F]
2	A-	GRN	
3	B+	RED	B 130°C [266°F]
4	B-	BLU	MAX.80°C

SPECIFICATION CONNECTION

AMP S/P/PHASE	RESISTANCE/PHASE (Ohms) @25°C	INDUCTANCE/PHASE (mH) @1KHz	HOLDING TORQUE (N.m) [lb-in]	STEP ANGLE (°)	STEP ACCURACY (NON-ACCUM)	ROTOR INERTIA (g-cm²)	WEIGHT (kg) [lb]	INSULATION CLASS	TEMPERATURE RISE
6.0	0.52±10%	5.50±20%	8.50 [75.29]	1.80	±5.00%	2700	4.32 [9.52]	B 130°C [266°F]	MAX.80°C



mm	UNITS	SCALE
1:2	APVD	SIGNATURE
LDJ	ZPJ	DATE

STEPPER MOTOR
34HS46-6004D-B700