


CONNECTION	BIPOLAR
SPECIFICATION	
NO. of PHASES	3
NO. of POLES	4
RESISTANCE/PHASE(Ohms)@25°C	0.60±10%
INDUCTANCE/PHASE(mH)@1KHz	1.40±10%
RATED VOLTAGE(V)	24
RATED TORQUE(mN.m)	160
RATED POWER(W)	67
RATED SPEED(RPM)	4000±10%
RATED CURRENT(A)	4.1
HALL LEAD STYLE	UL 1007 AWG24
PHASE LEAD STYLE	UL 3266 AWG22
BACK EMF(V/krpm)	3.4
AMBIENT TEMPERATURE	-10°C~50°C[14°F~122°F]
INSULATION CLASS	B 130°C[266°F]
TEMPERATURE RISE	MAX.80°C

UNIT mm
 GB/T 1804-M EQV.ISO 2768-1 CLASS M:

<=6	±0.1
>6~30	±0.2
>30~120	±0.3
>120~400	±0.5



mm			
UNITS	DRN	MYX	1.15.2026
1:1	APVD	LDJ	1.15.2026
SCALE	SIGNATURE	DATE	

OSMTEC®
 Stepper Motor Specialists

BRUSHLESS DC MOTOR

57BLY54-24-01