


NOTE: BY DEFAULT, GEAR BOX COMES WITH SS-13 SHAFT SLEEVE.

SPECIFICATION	VALUE
GEAR RATIO	20
EFFICIENCY	94%
BACKLASH@NO-LOAD(arcmin)	<=20
MAX.PERMISSIBLE TORQUE(Nm)[lb-in]	90.00[796.57]
MOMENT PERMISSIBLE TORQUE(Nm)[lb-in]	180.00[1593.13]
SHAFT MAXIMUM AXIAL LOAD(N)	800
SHAFT MAXIMUM RADIAL LOAD(N)	1000
GEARBOX MATCHING MOTOR'S INPUT SHAFT LENGTH (mm)	22-41
RATED INPUT SPEED(RPM)	3000
MAX. INPUT SPEED(RPM)	6000
NOISE(dB)	<=65
WATERPROOF RATING	IP54
LIFE(h)	20000
WORKING TEMPERATURE	-20°C~150°C[-4°F~302°F]

**OSMTEC**®  
Stepper Motor Specialists



mm			
UNITS	DRN	MYX	1.13.2026
1:2	APVD	LDJ	1.13.2026
SCALE	SIGNATURE	DATE	

**PLANETARY GEARBOX**

**EG34-G20-D13**