


PHOTOELECTRIC SWITCH SEQUENCE		
PIN NO	BIPOLAR	LEADS
1	+5~24V	BRN
2	GND	BLU
3	SIGNAL LINE	BLK
4	N/A	WHT

FULL STEP 2 PHASE-Ex.,WHEN FACING MOUNTING END (X)

STEP	A+	B+	A-	B-		CCW	
1	+	+	-	-	 CW	 CCW	
2	-	+	+	-			
3	-	-	+	+			
4	+	-	-	+			

UNIT mm
 GB/T 1804-M EQV.ISO
 2768-1 CLASS M:
 <=6 ±0.1
 >6~30 ±0.2
 >30~120 ±0.3
 >120~400 ±0.5



PIN NO	BIPOLAR	LEADS
1	A+	RED
2	A-	RED/WHT
3	B+	GRN
4	B-	GRN/WHT

SPECIFICATION	CONNECTION	BIPOLAR
AMPS/PHASE		1.50
RESISTANCE/PHASE(Ohms)@25°C		1.70±10%
INDUCTANCE/PHASE(mH)@1KHz		2.50±20%
HOLDING TORQUE(Nm)[lb-in]		0.25[2.22]
MAXIMUM THRUST(N)		300
STEP ANGLE(°)		1.80
STEP ACCURACY(NON-ACCUM)		±5.00%
LEAD(mm)[in]		2.00[0.07874]
LINEAR TRAVEL/STEP(mm)[in]		0.01[0.00039]
RATED LOAD CAPACITY(N)		230
MAX SPEED(mm/s)		30
POSITION ACCURACY(mm)		±0.02
AMBIENT TEMPERATURE		-20°C~50°C[-4°F~122°F]
INSULATION CLASS		B 130°C[266°F]
TEMPERATURE RISE		MAX.80°C

OSMTEC[®]
 Stepper Motor Specialists

mm	DRN	LDJ	1.14.2026
UNITS	APVD	ZPJ	1.19.2026
SCALE	SIGNATURE		DATE

STEPPER MOTOR LINEAR ACTUATOR
LMD17S13BAB15-120